


**BULLARD
BOLLARDS**
POWERED BY
SOLUX

ADA B80

SOLAR BOLLARD

Designed in aluminum and treated to withstand the harshest conditions, the Solux solar bollards will be perfect for all your lighting, marking, and beautification applications for your outdoor living spaces with total energy autonomy. Equipped with high-efficiency solar cells, the light fixture charges in the sun but also in cloudy weather, ensuring **optimal lighting throughout the year**.



NOMINAL FLUX **420 LUMENS**
NOMINAL POWER **3.5 WATTS**

LIGHTING

Efficiency **120 Lumens/Watts**
Chips LED **PHILIPS Luxeon 30-30**
LED lifetime **Over 80 000 hours LM80**
Optics/CCT **T-V / 2300K to 6500K (Dual CCT optional)**
Light Height **31,5" (80 cm)**

BATTERY

Technology **Lithium Iron Phosphate LIFEPO4**
Capacity **28Wh**
Autonomy **Over 24 hours at full charge - 4 Rainy Days back up**
Charging time **6 hours**
Lifespan **Over 3000 CYCLES @ 80% DOD over 10 years Lifetime**
Working temp. **14°F to 158°F (optional -40°F to 158°F) -10°C to 70 °C - (optional -40°C TO 70 °C)**

ENERGY

Solar panel **6 Wc**
Cells type **Monocrystalline Panel Grade A 25 years**
Certificates **IEC 61215 - IEC 61730 I and II - IEC 60904**

ELECTRONIC

Sensor **PIR 180° sensor (optional)**

DIMENSIONS

Product **D10,24" x H31,5" (D26cm x H80cm)**
Carton size **33,46" x 12,6 x 13,00" (85cm x 32 cm x 33 cm)**
Weight **9,5 lb (4.3 KG)**
Materials **Die cast aluminum**
Installation **Concrete base or insert on support**
Product code **SL-021 80**

Solux retains the right to modify or change product specifications without prior notice, as part of our ongoing commitment to improvement



Parks & gardens



Pathways



Campsites

CERTIFICATIONS

IEC / TUV / EMC / LM-79- 08 and LM-80 test standards / IK8 / IP65 / CE / ULOR



* Solux offers a 5 Year Limited Warranty for the Solar Bollard-Series luminaire to be free from defects in material and workmanship for up to five (5) years from date of shipment. This limited warranty covers all components when installed and operated according to Solux instructions. Fixture suitable for ambient temperature from -10° to 50°. PV Panels - 20 year performance warranty Controller & Batteries : 5 years

ADA B80 - SOLAR BOLLARD - DATA SHEET / Page 1 of 5

sales@gordonbullard.com
www.bullardbollards.com
1-877-964-4646



991 South Gull Lake Dr
Richland, MI 49083
USA



**BULLARD
BOLLARDS**
POWERED BY
SOLUX

IP65

LUMINAIRE & LEDS


The **ADA B80** bollard incorporates the latest LED technologies, its elegance and ease of installation will meet your lighting needs. ADA is equipped with **LED chips, combining performance and robustness with 120 lumens per watt.**

A TOTAL OF 420 LUMENS

Our light fixture also complies with current standards concerning light pollution.




SYMMETRICAL DISTRIBUTION



PHOTOMETRIC CURVE

LIGHT DISTRIBUTION CURVE


UNIT : CD



www.solux-light.com

LIGHT DISTRIBUTION CURVE

LINEAR



CD C0/C180 — C90/C270 — C0 —

[DOWNLOAD IES FILES](#)



ADA B80 - SOLAR BOLLARD - DATA SHEET / Page 2 of 5

sales@gordonbullard.com

www.bullardbollards.com

1-877-964-4646



991 South Gull Lake Dr

Richland, MI 49083

USA



BATTERY LIFEPO4

OVER 10 YEARS LIFESPAN

The ADA bollard is equipped with Lithium Iron Phosphate LIFEPO4 batteries, recognized as the **best battery technology** in terms of **longevity, safety, and performance** for solar applications. Our batteries enjoy a lifespan of over **3000 cycles, which is more than 10 years at 80% DOD.**




EXTREME TEMPERATURE

14°F to 158°
- 10 °C TO 70 °C

While standard batteries benefit from an operating temperature of **14°F to 158°F (-10°C to 70°C)**, Solux offers as optional a new Special LIFEPO4 battery with working range of **-40°F to 158°F (-40°C to 70°C)**.

BMS ELECTRONIC PROTECTION BATTERY MANAGEMENT SYSTEM

Our batteries are equipped with **electronic circuit boards for a higher protection**, ensuring battery functioning optimization in any situation.



THE BMS PROTECTS AGAINST

- OVER/UNDER CURRENT • OVERLOAD • OVER/UNDER VOLTAGE
- OVER/UNDER CHARGE • TEMPERATURE MANAGEMENT

COMPARISONS OF DIFFERENT BATTERY TECHNOLOGIES

LIFETIME & CYCLES AT 80% DOD*

Comparison of different battery technologies



Lead Acid
200



NimH
700




Lithium ION
800




Lithium LifePO4
3 000

CHARGING TEMPERATURE RANGE WITHOUT CAPACITY LOSS


Minimum & Maximum temperature range for Optimal charging during the day




Lead Acid



NimH



Lithium ION



Lithium LifePO4

sales@gordonbullard.com

www.bullardbollards.com

1-877-964-4646



ADA B80 - SOLAR BOLLARD - DATA SHEET / Page 3 of 5

991 South Gull Lake Dr

Richland, MI 49083

USA




SOLAR PANEL

Solar cells **GRADE A**

6 WATTS

Encapsulated Monocrystalline Solar Panel **Grade A** Solar Cell with Tempered Glass.



OUR PV PERFORMANCE GUARANTEE



PRESENCE DETECTOR INFRA-RED SENSOR

THE ADA BOLLARD AUTOMATICALLY TURNS ON AT DUSK AND OFF AT DAWN.

Solux offers optional PIR movement sensor. The infra red detector integrated into the light fixture will increase the light power as pedestrians or vehicles pass, thus providing a higher level of safety while respecting the environment.



Depending on the geographical area, we will select the % of light reduction.

- Program 1** > 40% Dim + 100% ON during 20 sec
- Program 2** > 30% Dim + 100% ON during 20 sec
- Program 3** > 20% Dim + 100% ON during 20 sec

ADA B80 - SOLAR BOLLARD - DATA SHEET / Page 4 of 5

sales@gordonbullard.com
www.bullardbollards.com
1-877-964-4646



991 South Gull Lake Dr
Richland, MI 49083
USA



**BULLARD
BOLLARDS**


POWERED BY

SOLUX

EASY INSTALLATION

NO CABLING & TRENCHING

The ADA comes in two different mounting type, both requiring **neither trenching or cabling** for a **fast and economical installation**.
Simply insert the bollard into concrete or mount it on anchor rods.



1

DIRECT BURIED


2

FLAT MOUNT

DIMENSIONS

BOLLARD AND BASE

B80



*All dimensions are in mm

ADA B80 - SOLAR BOLLARD - DATA SHEET / Page 5 of 5

sales@gordonbullard.com

www.bullardbollards.com

1-877-964-4646



991 South Gull Lake Dr

Richland, MI 49083

USA